

LED T8 FIXTURE



Model Number	Size	Body Material
WM-T8F-600-1	656x80x90	ABS+PC
WM-T8F-900-1	912x80x90	ABS+PC
WM-T8F-1200-1	1260x80x90	ABS+PC
WM-T8F-1500-1	1560x80x90	ABS+PC

Model Number	Size	Body Material
WM-T8F-600-2	656x115x90	ABS+PC
WM-T8F-900-2	912x115x90	ABS+PC
WM-T8F-1200-2	1260x115x90	ABS+PC
WM-T8F-1500-2	1560x115x90	ABS+PC

LED T8 TUBES



Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
WM-T8N/P/G-9W	600	9W	100lm/W	2700K-7000K	>80	AC 170-265V	2 years	270°	NANO/PC/GLASS
WM-T8N/P/G14W	900	14W	100lm/W	2700K-7000K	>80	AC 170-265V	2 years	270°	NANO/PC/GLASS
WM-T8N/P/G-18W	1200	18W	100lm/W	2700K-7000K	>80	AC 170-265V	2 years	270°	NANO/PC/GLASS
WM-T8N/P/G-24W	1500	24W	100lm/W	2700K-7000K	>80	AC 170-265V	2 years	270°	NANO/PC/GLASS



宁波威尔美德电器有限公司
Ningbo WELL MADE Electrical Co.,Ltd.
Add:A2 1208LiYuanShangDu Building Huancheng
West Road Ningbo Zhejiang China
Tel: 86-574-87103265 86-574-87162198
Fax:86-574-87103266
E-mail:wellmade@wellmade.asia
www.nb-wellmade.en.alibaba.com
www.wellmade.asia



LED WORKING LIGHT



GZ101-10W



GZ101-20W



GZ102-20W



Model Number	Power	Luminous Flux	CCT	Ra	Voltage	Charging Time	Beam Angle	Body Material
GZ101-10W	10W	MAX 800lm	2700K-6500K	>70	DC3.7V USB	4-5H	100°	aluminum alloy+ABS
GZ101-20W	20W	MAX 1600lm	2700K-6500K	>70	DC3.7V USB	4-4.5H	100°	aluminum alloy+ABS
GZ102-20W	20W	MAX 1600lm	2700K-6500K	>70	AC 220-240V		100°	aluminum alloy+ABS



GZ201-10W



GZ201-10W



GZ201-20W

FEATURES

- ▶ 10W/20W
- ▶ DC3.7V with USB
- ▶ Lithium-3.7V
- ▶ IP54
- ▶ Three-mode switch

Model Number	Power	Luminous Flux	CCT	Ra	Voltage	Charging Time	Beam Angle	Body Material
GZ201-10W	10W	MAX 600lm	2700K-6500K	>70	DC3.7V	2-2.5H	100°	aluminum alloy
GZ201-20W	20W	MAX 1200lm	2700K-6500K	>70	DC3.7V	2-2.5H	100°	aluminum alloy



GZ301-10W/20W



GZ401-10W



GZ401-10W

FEATURES

- ▶ 10W/20W
- ▶ DC3.7V with USB
- ▶ Lithium-3.7V
- ▶ IP54
- ▶ Three-mode switch

Model Number	Power	Luminous Flux	CCT	Ra	Voltage	Charging Time	Beam Angle	Body Material
GZ301-10W	10W	MAX 800lm	2700K-6500K	>70	DC3.7V	4-4.5H	100°	aluminum alloy
GZ301-20W	20W	MAX 1500lm	2700K-6500K	>70	DC3.7V	4-4.5H	100°	aluminum alloy
GZ401-10W	10W	MAX 700lm	2700K-6500K	>70	DC3.7V	4-4.5H	100°	aluminum alloy



LED STREET LIGHT



ST101-60W-L

ST101-90W-L

ST101-120W-L

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
ST101-60W-L	410x28x57	60W	100lm/W	2700K-6500K	>65	AC 85-265V	2 years	70°x140°	Aluminum+PC cover
ST101-90W-L	600x160x60	90W	100lm/W	2700K-6500K	>65	AC 85-265V	2 years	70°x140°	Aluminum+PC cover
ST101-120W-L	600x160x60	120W	100lm/W	2700K-6500K	>65	AC 85-265V	2 years	70°x140°	Aluminum+PC cover



ST201-80W-C

ST201-120W-C

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
ST201-80W-C	583x244x120	80W	120lm/W	2700K-6500K	>70	AC 85-265V	5 years	70°x150°	Aluminum+glass cover
ST201-120W-C	673x260x122	120W	120lm/W	2700K-6500K	>70	AC 85-265V	5 years	70°x150°	Aluminum+glass cover



ST301-60W-C

ST301-80W-C

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
ST301-60W-C	630x300x140	60W	120lm/W	2700K-6500K	>70	AC 85-265V	3 years	90°x140°	Aluminum+glass cover
ST301-80W-C	630x300x140	80W	120lm/W	2700K-6500K	>70	AC 85-265V	3 years	90°x140°	Aluminum+glass cover



ST401-80W-C

ST401-150W-C

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
ST401-80W-C	570x300x175	80W	120lm/W	2700K-6500K	>70	AC 85-265V	3 years	90°x140°	Aluminum+glass cover
ST401-150W-C	630x330x175	150W	120lm/W	2700K-6500K	>70	AC 85-265V	3 years	90°x140°	Aluminum+glass cover



ST501-60W-C

ST501-120W-C

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
ST501-60W-C	570x265x150	60W	120lm/W	2700K-6500K	>70	AC 85-265V	3 years	80°x140°	Aluminum+glass cover
ST501-120W-C	795x350x200	120W	120lm/W	2700K-6500K	>70	AC 85-265V	3 years	80°x140°	Aluminum+glass cover



LED HIGH BAY LIGHT

NEW



HB-301-100W-C



HB-301-200W-C



Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
HB301-100W-C	φ270x170	100W	130lm/W	2700K-6500K	>80	AC 100-270V	5 years	60°	Die casting aluminum
HB301-200W-C	φ330x200	200W	130lm/W	2700K-6500K	>80	AC 100-270V	5 years	60°	Die casting aluminum



HB201-100W-W



HB201-150W-W



HB201-200W-W



Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
HB201-100W-W	φ290x185	100W	120lm/W	2700K-6500K	>80	AC 85-265V	3 years	90°	Die casting aluminum
HB201-150W-W	φ350x187	150W	120lm/W	2700K-6500K	>80	AC 85-265V	3 years	90°	Die casting aluminum
HB201-200W-W	φ400x195	200W	120lm/W	2700K-6500K	>80	AC 85-265V	3 years	90°	Die casting aluminum



HB101-100W-L



HB101-150W-L



HB101-200W-L

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
HB101-100W-L	φ285x165	100W	100lm/W	2700K-6500K	>70	AC 180-240V	2 years	90°	Iron+PC cover
HB101-150W-L	φ305x165	150W	100lm/W	2700K-6500K	>70	AC 180-240V	2 years	90°	Iron+PC cover
HB101-200W-L	φ335x175	200W	100lm/W	2700K-6500K	>70	AC 180-240V	2 years	90°	Iron+PC cover



LED FLOOD LIGHT



AL101-30W-L-S



AL101-50W-L-S

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
AL101-30W-L-S	176x152x27	30W	70lm/W	2700K-6500K	>70	AC 175-265V	2 years	120°	Die casting aluminum
AL101-50W-L-S	212x182x29	50W	70lm/W	2700K-6500K	>70	AC 175-265V	2 years	120°	Die casting aluminum



AL101-10W-L



AL101-20W-L



AL101-30W-L




AL101-50W-L




AL101-100W-L


Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
AL101-10W-L	110x92x25	10W	70lm/W	2700K-6500K	>70	AC 175-265V	2 years	120°	Die casting aluminum
AL101-20W-L	143x122x25	20W	70lm/W	2700K-6500K	>70	AC 175-265V	2 years	120°	Die casting aluminum
AL101-30W-L	175x130x32	30W	70lm/W	2700K-6500K	>70	AC 175-265V	2 years	120°	Die casting aluminum
AL101-50W-L	215x145x32	50W	70lm/W	2700K-6500K	>70	AC 175-265V	2 years	120°	Die casting aluminum
AL101-100W-L	275x190x36	100W	70lm/W	2700K-6500K	>70	AC 175-265V	2 years	120°	Die casting aluminum




A201-10W-C




A201-20W-C



A201-30W-C



A201-50W-C



A201-100W-C

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
AL201-10W-C	88x74x25	10W	80lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL201-20W-C	109x92x27	20W	80lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL201-30W-C	148x126x20	30W	75lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL201-50W-C	200x170x32	50W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL201-100W-C	270x220x40	100W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum



LED FLOOD LIGHT



AL201-20W-C-S



AL201-30W-C-S

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
AL201-20W-C-S	109x92x27	20W	80lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL201-30W-C-S	148x126x20	30W	75lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum



AL301-20W-L-S



AL301-30W-L-S



AL301-20W/30W-L-S

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
AL301-20W-L-S	121x95x24	20W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL301-30W-L-S	159x122x26	30W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum



AL301-10W-L



AL301-20W-L



AL301-30W-L



AL301-50W-L



AL301-100W-L

Model Number	Size	Power	Luminous Efficiency	CCT	Ra	Voltage	Warranty	Beam Angle	Body Material
AL301-10W-L	103x83x24	10W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL301-20W-L	121x95x24	20W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL301-30W-L	159x122x26	30W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL301-50W-L	205x160x34	50W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum
AL301-100W-L	270x210x34	100W	70lm/W	2700K-6500K	>70	AC 220-240V	2 years	120°	Die casting aluminum



LED GARDEN LIGHT



TY101-10W



TY102-10W-580



TY102-10W-780

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY101-10W	240x91x115	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY102-10W-580	240x108x580	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC
TY102-10W-780	240x108x780	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC



TY201-10W



TY202-10W-580



TY202-10W-780

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY201-10W	150x85x76	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY202-10W-580	150x107x580	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC
TY202-10W-780	150x107x780	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC



LED GARDEN LIGHT



TY301-10W



TY302-10W-580



TY302-10W-780

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY301-10W	240x138x165	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY302-10W-580	285x140x580	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC
TY302-10W-780	285x140x780	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC



TY401-10W



TY402-10W-580



TY402-10W-780

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY401-10W	164x80x263	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY402-10W-580	154x110x580	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC
TY402-10W-780	154x110x780	10W	720lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC



LED GARDEN LIGHT



TY501-10W



TY503-10W



TY502-10W-580



TY502-10W-780

Model Number	Size	Power	Voltage	Life Span	Fixing way	Body Material
TY501-10W	120x200x385	Max 40W	AC 220-240V	N/A	wall mounted	Iron+glass
TY503-10W	120x200x320	Max 40W	AC 220-240V	N/A	wall mounted	Iron+glass
TY502-10W-580	130x130x580	Max 40W	AC 220-240V	N/A	on the ground	Iron+glass
TY502-10W-780	130x130x780	Max 40W	AC 220-240V	N/A	on the ground	Iron+glass



TY601-6W



TY602-6W-400



TY602-6W-700

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY601-6W	122x100x200	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY602-6W-400	100x100x400	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC
TY602-6W-700	100x100x700	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC



LED GARDEN LIGHT



TY701-6W



TY702-6W-400



TY702-6W-700

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY701-6W	122x100x200	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY702-6W-400	116x124x400	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC
TY702-6W-700	116x124x700	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	on the ground	Aluminum+PC



TY801-10W



TY801-10W



TY802-20W

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY801-10W	140x290x152	10W	800lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	PC
TY802-20W	330x230x134	20W	1600lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	PC



LED GARDEN LIGHT



TY901-11W



TY902-7W



TY902-7W

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY901-11W	133x51x105	11W	880lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY902-7W	150x56x280	7W	560lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC



TY903-6W



TY903-6W



TY904-40W



TY903-6W



TY904-40W

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY903-6W	253x225x218	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY904-40W	268x230x170	MAX 40W	N/A	N/A	N/A	AC 220-240V	N/A	wall mounted	Aluminum+PC



TY905-6W



TY906-6W



TY907-8W

Model Number	Size	Power	Luminous Flux	CCT	Ra	Voltage	Warranty	Fixing way	Body Material
TY905-6W	123x130x69	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY906-6W	123x130x69	6W	480lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC
TY907-8W	129x100x85	8W	640lm	2700K-6500K	>80	AC 220-240V	2 years	wall mounted	Aluminum+PC

